

CINETOUR HD PRODUCTION



• PRODUCTION AREA •

Video Switcher

- 1 - Sony HDVS-7250 High Definition Switcher
- 1 - Sony HDME-7000 Dual Channel Digital Effects

• TRANSMISSION •

- 1 - Leitch HDU-3800 Upconverter
- 4 - Sony HKPF-1125 Upconverters
- 6 - DPS 470 Digital Frame Synchronizers
- 1 - Sony HKDS-3700 64x64 High Definition / Serial Digital / AES Audio Router
- 1 - Leitch CSD5300 clock system

• VIDEOTAPE •

- Up to 8 Video Tape Recorders:
 - Sony SRW-5500 HDCAM / HDCAM SR
 - Sony HDW-F500 HDCAM
 - Sony DVW-A500 DigitalBetacam
- 3 - VHS VCRs
- 1 - DVD recorder

• COMMUNICATIONS •

- 1 - Telex/RTS Adam 64x64 Intercom
- 1 - Lucent 16-line telephone system

• GRAPHICS •

- 1 - Pinnacle Deko 3000 Hybrid HD/SD Character Generator (available)

• AUDIO (Available) •

- 1 - (or 2) Yamaha DM2000 digital audio console
 - Genelec or Meyers monitoring
 - Outboard equipment per projects requirements
- 1 - Calrec Zeta digital audio console

• CAMERAS AND LENSES •

Up to 8 - Sony 900/950/1000/1500 series cameras:

- Sony HDC900/1000 Hand Cameras
- Vinten Vector 700 pan and tilt heads
- Quick Set tripods with wheels
- Fujinon 101x Lenses
- Fujinon 88x Lenses
- Fujinon 87x Lenses
- Fujinon 66x Lenses

- Sony HDC950/1500 Hand Held Cameras
- Fujinon 22 x 7.8 hand held lenses
- Fujinon 20 x 7.5 hand held lenses
- Fujinon 13 x 4.5 wide angle hand held lenses
- Sachtler/Vinten Tripod Systems

Evertz / Aja / Leitch downconverters
(for Steadycam's, Jibs, Dollies)

• POWER REQUIREMENTS •

200 amps per leg, 3 phase, 208V

B unit may "T" off main production truck, or if powered separately: 100 amp, 1 phase, 208V

• GENERATOR / AIR CONDITIONING •

- 1 - On-board integrated 60kw generator
- 1 - On-board redundant 17 Ton air-conditioning

• SPACE REQUIREMENTS •

Cinetour A Unit
73' long with tractor
59' long (expanded for show) without tractor
8'6" wide contracted, 16' wide expanded
13'6" high

B unit (24' box truck subject to size of event)
65' long with tractor
51' long without tractor
8'6" wide
13'0" high

Mobile unit equipment lists are subject to change without notice. Specifications shown represent a potential configuration. Please consult with your AMV Account Executive regarding current or per-event specifications.