



KU 6 – 29' SATELLITE PRODUCTION TRUCK

TRANSMISSION

- 2 PARADISE DATACOM 450 WATT KU TRANSMITTERS PHASE COMBINED CAPABLE OR SEPARATE FEEDS WITH NO POLARITY RESTRICTIONS
- 2 ATEME HD VIDEO ENCODERS HD DVBS2 ENCODING
- 2 STUDIO TECHNOLOGIES LIVE LINK MINI FIBER INTERCONNECT
- 1 1,250 FEET 4 CHANNEL SINGLE MODE FIBER
- 2 500 FEET 4 CHANNEL SINGLE MODE FIBER (MIN)
- 2 ATEME SATELLITE IRD'S
- 2 ADTEC RD-60 SATELLITE IRD'S

MONITORING

- 1 12 CHANNEL MULTIVIEWER

AUDIO

- 1 AUDIO MIXER
- 1 LECTROSONICS WIRELESS IFB SYSTEM WITH 3 RECEIVERS
- 4 HARD WIRED IFB BELTPACKS
- 4 LECTROSONICS WIRELESS LAVALIER MICS
- 1 CLEAR COM 4 CHANNEL CAMERA INTERCOM SYSTEM
- 4 CLEAR COM CAMERA INTERCOM BELT PACKS
- 1 IFB PLUS 2 SYSTEM WITH ABILITY TO SEND DIRECTORS HOT MIC

ROUTING PROCESSING

- 1 ATEM 1 BLACK MAGIC DESIGN SWITCHER

CAMERA

- 3 HYPER DECK PRO RECORDERS
- 2 PANASONIC 300 HD CAMERAS

MISCELLANEOUS

4 1000 WATT LED BI COLOR LIGHTS

4 C STANDS

DIMENSIONS

29' L X 12'6" H X 8' W (11' W/STEPS EXTENDED)

20'6" HEIGHT W/DISH DEPLOYED

31,300LBS GROSS WEIGHT

POWER REQUIREMENTS

100 AMP SINGLE PHASE 208-240 VOLTS

BARE WIRE OR CAM LOCK CONNECTIONS

200' POWER CABLE ON BOARD

ON BOARD GENERATOR 25 Kw POWER TECH GENERATOR