



## ZURICH– DOUBLE EXPANDO MOBILE PRODUCTION UNIT

### FEATURES & HIGHLIGHTS:

AMV's Large and Powerful HDR and 4K Production Truck; Sony XVS 8000 (UHD/3G/HD Capable) 5 ME W/ Aux Buses that Can Dissolve (Up to 12); Sony 4300 Cameras; Wired for 20 Video Recording Machines and 4 EVS Chassis; 3- 30" OLED 4K Monitors in Production; Studer Vista X; (Audio Back Bench in Audio Room); 32 IN and 32 OUT Single Mode ST Fiber to I/O from Grassvalley Router; 32 x 32 Dante/ Analog converter I/O Box; 104 DeEmbedders, 160 Embedders, 16 Frame syncs. MADI 7 In - 8 Out on Router; 16 XVP Up/Down/Cross Converters w/ 23.98p to 23.98psf

### PRODUCTION:

- Sony XVS 8000 (UHD/3G/HD Capable) Switcher, (112 Inputs X 48 Outputs); 5 ME W/ 4 external DME Channels & Re-Sizers on all Keyers; Back Bench/ Screens Switching Panels (2- 25 button X-Point Moduls & 2- Transition/ Flexi Pad Moduls) Attached to Main Switcher Frame; 128 X 8 Multi View Monitor Wall; 48 X 4 External Multi View to I/O.

### AUDIO:

- Studer Vista X W/ 72 Faders on the Surface with built in dual PCM96 effects processors
- Studer Stage Boxes W/ SMPTE Fiber (Optional) (2) 48 X 16 & (1) 40 Stage Boxes
- 128 channels of DANTE I/O
- 4 Engine TC Electronics System 6000
- Extensive MADI routing
- 2 Lexicon PCM 96

### CAMERAS:

- 12 Sony 4300-4K (Wired for 16)+
- Sony HDC-F5500, Sony Venice II, Sony F-55 Live available optionally upon request

### ROUTER/ CONVERSION:

- 104 DeEmbedders, 160 Embedders, 16 Frame syncs. MADI 7 In-8 Out on Router;
- 64X64 AES Router; 64X64 ST Analog Router
- 6 4K Up/Down Converters (Available Upon Request)
- 2 4K Color Corrector Channels Available
- 8 HD Color Corrector Channels Available

### RECORD & PLAYBACK:

- Up to 4 8-Channel EVS
- 10 VTR Slots/Wired for 20
- 4 Channel H.264 Recorder
- 6 Time Code Keyers

### COMMUNICATIONS:

- RTS Adam M OMNEO Intercom with 208 X 208 Ports
- 8– RTS Tiff 4000s

### GRAPHICS:

- Wired for 2 CG Machines

### POWER REQUIREMENTS:

- **A-Unit:** 1 Service, 200 AMP, 3 Phase, 208 Volts
- **B-Unit:** 1 Service, 100 AMP, 3 Phase, 208 Volts (Only Required if Used for Production)

### SPACE REQUIREMENTS:

- **A-Unit: (All Measurements Without Tractor)**  
56'8" Long x 13'6" High x 8'6" Wide– Closed (W/ the Longest Tractor Length is 77'4")  
59' Long x 13'6" High x 15'10" Wide– Expanded W/ AC Flaps Open & Stairs Perpendicular to Curb
- **B-Unit: (All Measurements Without Tractor)**  
51'6" Long x 13'6" High x 8'6" Wide– Closed  
58' Long x 13'6" High x 8'6" Wide– W/ Liftgate Down & Side Door Closed

*Mobile unit equipment list subject to change without notice. Additional equipment available. Please consult with your AMV Account Executive regarding availability and per-event specifications.*